RESPONSE

Examiner: GARTENBERG, Ehud

Serial No. 10/676 827

Atty. Docket No.: 58523.010100UT/US

AMENDMENTS TO THE CLAIMS

Please amend the claims as follows:

- 1. (Currently Amended) A boundary layer turbine, comprising:
 - a housing, formed to create a cavity therein;
 - at least one inlet port, wherein the inlet port is coupled to the housing;
 - at least one outlet port, wherein the outlet port is coupled to the housing;
 - a shaft, comprised of two ends, wherein at least one end of the shaft extends outside the housing, and at least a portion of the shaft extends within the housing;
 - a plurality of discs with at least one hole at or near the center thereof,
 - an exhaust cone, mounted at or near the center of the plurality of discs, wherein the exhaust cone includes at least one vacuum release tube; and,
 - a mounting means, wherein the mounting means connects the plurality of discs to the shaft using a dovetail connection.
- 2. (Original) The boundary layer turbine of Claim 1, wherein the plurality of discs are in physical contact with each other.
- 3. (Original) The boundary layer turbine of Claim 2, wherein each of the plurality of discs are etched such that at least one channel is formed between the discs.
- 4. (Original) The boundary layer turbine of Claim 1, wherein the mounting means uses an internal dovetail connection to connect the plurality of discs to the shaft.
- 5. (Canceled)
- 6. (Previously Presented) The boundary layer turbine of Claim 5, wherein the shape of the exhaust cone is controllable.
- 7. (Canceled)
- 8. (Withdrawn) The boundary layer turbine of Claim 1, wherein the discs are made of a ceramic material.
- 9. (Original) The boundary layer turbine of Claim 1, wherein the discs are coated with a ceramic material.
- 10. (Withdrawn) The boundary layer turbine of Claim 1, wherein the discs are coated with a catalyst.

RESPONSE

Examiner: GARTENBERG, Ehud

Serial No. 10/676 827 Atty. Docket No.: 58523.010100UT/US

- 11. (Withdrawn) The boundary layer turbine of Claim 10, wherein the catalyst is Platinum.
- 12. (Withdrawn) The boundary layer turbine of Claim 10, wherein the catalyst is an alloy comprised of a combination of at least Nickel and Tin.
- 13. (Withdrawn) The boundary layer turbine of Claim 1, wherein the surface of the plurality of discs have been etched.
- 14. (Withdrawn) The boundary layer turbine of Claim 1, wherein six inlet ports are used.
- 15. (Withdrawn) A boundary layer turbine, comprising:
 - a housing, formed to create a cavity therein:
 - at least one inlet port, wherein the inlet port is coupled to the housing;
 - at least one outlet port, wherein the outlet port is coupled to the housing;
 - a shaft, comprised of two ends, wherein at least one end of the shaft extends outside the housing, and at least a portion of the shaft extends within the housing;
 - a single piece disc pack, with at least one hole at or near the center thereof; and,
 - a mounting means, for coupling the single part disc array to the shaft.
- 16. (Withdrawn) The boundary layer turbine of Claim 15, wherein the mounting means uses an internal dovetail connection to connect the plurality of discs to the shaft.
- 17. (Withdrawn) The boundary layer turbine of Claim 15, further comprising an exhaust cone mounted at the center of the plurality of discs.
- 18. (Withdrawn) The boundary layer turbine of Claim 17, wherein the shape of the exhaust cone can be controlled.
- 19. (Withdrawn) The boundary layer turbine of Claim 17, wherein the exhaust cone includes at least one vacuum release tubes.
- 20. (Withdrawn) The boundary layer turbine of Claim 17, wherein the exhaust cone, the disc pack, and the mounting means are made from a single component.
- 21. (Withdrawn) The boundary layer turbine of Claim 15, wherein the discs are made of a ceramic material.
- 22. (Withdrawn) The boundary layer turbine of Claim 15, wherein the discs are coated with a ceramic material.

RESPONSE

Examiner: GARTENBERG, Ehud

Serial No. 10/676 827 Atty. Docket No.: 58523.010100UT/US

23. (Withdrawn) The boundary layer turbine of Claim 22, wherein the discs are coated with a catalyst.

- 24. (Withdrawn) The boundary layer turbine of Claim 23, wherein the catalyst is Platinum.
- 25. (Withdrawn) The boundary layer turbine of Claim 23, wherein the catalyst is an alloy comprised of a combination of at least Nickel and Tin.
- 26. (Withdrawn) The boundary layer turbine of Claim 15, wherein the surface of the plurality of discs have been etched.
- 27. (Withdrawn) A method for obtaining power from a geothermal power source, comprising:
 - locating a heat exchanger, having an input port and an output port, at or near a source of geothermal power;
 - locating a boundary layer turbine, having at least one inlet port and an outlet port, at a position distant from the geothermal power source;
 - connecting the heat exchanger output port to at least one inlet port of a boundary layer turbine using at least one pipe;
 - connecting the at least one boundary layer turbine outlet port to the heat exchanger input port using at least one pipe.
- 28. (Withdrawn) A method of obtaining power from a high pressure medium and reducing the pressure such that the medium is useable in an end user device, comprising:
 - coupling a boundary layer turbine, having at least one input port, an outlet port, a disc pack, and a shaft driven by the disc pack, to a high pressure medium source;
 - coupling a generator to the boundary layer turbine shaft;
 - coupling at least one end user device to the outlet port of the boundary layer turbine; and,
 - allowing the high pressure medium to enter the boundary layer turbine through the at least one input port.
- 29. (Withdrawn) The method of Claim 28, wherein the medium is natural gas.
- 30. (Withdrawn) The method of Claim 28, wherein the medium is water.